

Container Handler

Used Container Handler Ontario Canada - Also known as container ships or cargo ships, container handlers use large intermodal containers to transport their goods. This shipping method is known as containerization. They are commonly utilized as a means of commercial freight transport often used to transport non-bulk forms of seagoing cargo. Container ship capacity is measured in units that are equal to 20' equivalent loads. Typical loads range with a mixture of 20-foot and 40-foot containers. Container ships are responsible for transporting roughly ninety percent of non-bulk items across the globe. As one of the largest commercial seaworthy vessels, container ships are the main rival of oil tankers among the largest ships on the ocean. Dry cargo falls into two main categories: bulk cargo and break-bulk cargo. Grain and coal are bulk cargo, typically transported in their raw format inside the ships hull, free from packages. Manufactured goods that are in packages comprise the majority of break-bulk cargo. Before containerization was invented in the 50s, break-bulk items were loaded, secured and unlashd one item at a time. When the cargo was grouped into containers, there were approximately 1000-3000 cubic feet of cargo that can be simultaneously moved after each unit has been standardized and secured. Efficiency has tremendously increased break-bulk cargo shipping. Thanks to these new systems, shipping time has been reduced by eighty-four percent and costs have come down by roughly thirty-five percent. Approximately 90% of non-bulk items were shipped in containers in 2001. The initial container ships in the 1940s were designed from tankers that were converted post-WWII. Container ships do not rely on individual hatches, holds and dividers that are part of regular cargo ships. The typical container ship's hull is a basically a large warehouse that is divided by vertical guide rails into cells. These cells have been engineered to hold the cargo in containers. Most cargo ships are designed from steel but additional materials such as plywood, fiberglass and wood are used. As containers have been designed to completely transferred to and from coastal carriers, semi-trailers, trucks, trains and more, these containers are categorized due to their function and size. Containerization has revolutionized the shipping industry; however, it did not start out in the easiest fashion. At first, many companies and shippers were worried about the huge costs associated with constructing ports, railway infrastructure and the roads needed to transport items via cargo ships. Numerous trade unions were concerned that containers would affect port jobs and manual labor associated with cargo handling for dock and port workers. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Container ships only take a few hours to be loaded and unloaded, compared to the days a traditional cargo vessel required. Shipping times have been shortened in between ports extensively along with labor finances. It only takes 3 weeks to have materials delivered from Europe to India as opposed to the months it used to require. There is generally less damage to goods due to less handling. Less cargo shifting during a voyage is also beneficial. Containers are sealed prior to shipping and opened only once they arrive at their destination, resulting in less theft and disruption. Container ships have reduced shipping time and lessened shipping expenses, resulting in enhanced international trade growth. Cargo that was previously shipped in bags, bales, cartons, barrels or crates now arrives in sealed containers from the factory. A product code on the contents is traced with the help of computers and scanning equipment. Technology has made this tracking system accurate and exact to enable a two week voyage to be timed for arrival within an accuracy rate of under fifteen minutes. Manufacturing times and delivery have been greatly enhanced with these advancements. Raw materials show up in sealed containers from factories in under an hour prior to being used in the manufacturing industry; resulting in fewer inventory expenses and greater accuracy. The shipping companies supply the exporters with boxes for loading products. They are delivered into the docks by rail or road or a combination of both to be loaded onto container ships. Containerization has streamlined the process of loading by reducing the number of workers and hours it takes to fit cargo into their holds. Cranes are used in

the shipping industry or on the pier to organize containers. More containers can be loaded onto the deck after the hull is loaded. Efficiency has been one of the main design elements for cargo ships. Containers may travel on break-bulk vessels. Cargo holds that have been designated to cargo ships have been specially designed to enhance the processes of loading and unloading in order to keep containers safe while crossing the seas. A specially designed hatch creates openings to access the main cargo holds from the deck. These openings flow along the whole cargo hold area and are surrounded by the hatch coaming which is a raised steel structure. There are hatch covers located on top of the hatch coamings. Wooden boards and tarps initially covered the hatches and held the battens secure until the 50s. Hatch covers are made of secure metal plates and cranes are used to lift them on and off of the ship. Additional hatch models use hydraulic rams and articulated mechanisms for closing and opening. Cell guides are a necessary component in cargo ship design. The cell guides are vertical pieces constructed of strong metal that is attached to the cargo hold within the ship. They work by guiding containers into particular rows while loading and help to support items during travel. The design of the container ship uses cell guides enough that the United Nations Conference on Trade and Development utilize them to distinguish between container ships and regular break-bulk cargo ships. There is a system used in cargo plans consisting of three dimensions to outline a container's position aboard the ship. The initial coordinate starts at the beginning of the ship and increases aft. The tier is the second coordinate, with the initial tier starting at the bottom of the cargo holds with the second, tier situated on top of the first and continuing on. The third coordinate is found in the third row. Rows are situated on the ship's port side have even numbers while those found starboard have odd numbers. The cargo situated near the centerline showcases lower numbers and as the cargo increases further from the center, the numbers get higher. Container handlers carry 20, 40 and 45 foot containers. The biggest sizes only fit above the deck. The forty-foot containers comprise most of the load or roughly 90% of container shipping. Roughly 90% of the freight in the world is delivered via container shipping. Approximately eighty-percent of global freight is shipped via forty-foot containers.